IMPACTS OF CLIMATE CHANGE ON NATURAL HAZARDS PROFILE

HUNTER REGION

December 2010



© State of NSW and Department of Environment, Climate Change and Water

This profile was developed by the NSW Department of Environment, Climate Change and Water (DECCW) in collaboration with:

- Bureau of Meteorology (BoM)
- University of Wollongong (UoW).

Disclaimer:

DECCW has prepared this report in good faith, exercising all due care and attention, but no representation or warranty, express or implied, is made as to the relevance, accuracy, completeness or fitness for purpose of this information in respect of any particular user's circumstances.

With respect to the content of this report, the following should also be noted:

- Only some meteorological and climatological hazards are covered. Other natural hazards such as landslide and earthquake are not covered.
- This profile is not a comprehensive description of the current state of natural hazards.
- Some projections currently involve a considerable degree of uncertainty.

This material may be reproduced for educational or non-commercial purposes, in whole or in part, provided the meaning is unchanged and the source is acknowledged.

Published by:

Department of Environment, Climate Change and Water NSW 59–61 Goulburn Street, Sydney PO Box A290

Sydney South NSW 1232

Ph: (02) 9995 5000 (switchboard)

Ph: 131 555 (information & publications requests)

Fax: (02) 9995 5999 TTY: (02) 9211 4723

Email: <u>info@environment.nsw.gov.au</u> Website: <u>www.environment.nsw.gov.au</u>

For further information contact:

Department of Environment, Climate Change and Water

59–61 Goulburn Street, Sydney

PO Box A290

Sydney South NSW 1232

Phone: 1300 361 967 or (02) 9995 5000

ISBN 978 1 74232 854 6 DECCW 2010/591

July 2010, web release with minor amendments December 2010

Contents

1	Intro	luction4				
2	Curre	ent clim	ate and natural hazards of the Hunter region	5		
	2.1	Curren	t climate	5		
	2.2	Natura	l hazards	5		
3	Proje	Projected changes to climate and natural hazards in the Hunter region				
	3.1	Projec	ted changes to climate	7		
	3.2	Projec	ted changes to natural hazards	7		
		3.2.1	Fire (see Table 2)	8		
		3.2.2	Wind (see Table 3)	9		
		3.2.3	Hail (see Table 4)	10		
		3.2.4	Lightning (see Table 5)	10		
		3.2.5	Flash flooding (see Table 6)	10		
		3.2.6	Riverine flooding (see Table 7)	11		
		3.2.7	Heatwaves (see Table 8)	11		
		3.2.8	Coastal erosion and inundation (see Table 9)	11		
4	Refe	rences		29		
Fig	jures	and tal	oles			
Fig	ure 1:	Мар	of the Hunter region	4		
Tal	ble 1:	Rece	nt significant natural events in the Hunter region	5		
Tal	ble 2:	Hunte	er fire hazard indicators	14		
Table 3:		Hunte	Hunter wind hazard indicators1			
Tal	ble 4:	Hunte	er hail hazard indicators	18		
Table 5:		Hunter lightning hazard indicators		19		
Table 6:		Hunter flash flooding hazard indicators		20		
Tal	ble 7:	Hunte	er riverine flooding hazard indicators	23		
Tal	ble 8:	Hunte	er heatwave hazard indicators	26		
Tal	Fable 9: Hunter coastal erosion and inundation hazard indicators					

1 Introduction

The Hunter region experiences recurring, costly and significant natural hazards potentially impacting upon public safety, private property, infrastructure integrity and the insurance sector. This profile provides emergency management agencies with information on:

the following natural hazards to which the Hunter region is exposed:

1. Fire 5. Wind

Flash flooding
 Lightning

3. Riverine flooding 7. Heatwave

4. Hail 8. Coastal erosion

• projections of how these natural hazards may change into the future due to climate change.

The Hunter region, shown in Figure 1, extends from Hallidays Point at the northern limit of the Great Lakes Shire south to Catherine Hill Bay, covering 29,600 km² and 11 local government areas (LGAs). It encompasses the Hunter/Central Coast Emergency Management District (EMD) (excluding the Central Coast LGA), and the Gloucester and Great Lakes LGA portion of the Mid North Coast EMD. The region incorporates 150 km of coastline, including 10 significant estuaries and coastal lakes, while the north-west is bounded by the Liverpool Ranges and abuts the New England Tablelands.

Figure 1: Map of the Hunter region



2 Current climate and natural hazards of the Hunter region

2.1 Current climate

The climate of the Hunter region is sub-tropical to temperate, with annual rainfall across the region averaging about 870 mm. It varies from east to west, ranging from more than 1100 mm/year about the coast and on the Barrington Tops, down to less than 600 mm/year in parts of the region further inland. Rainfall events are greatest in summer and autumn, with a higher proportion of winter rainfall on the coast than over the inland. Runoff is highest on the northern ranges and lowest on the coastal plains and foothills. It is uniformly distributed across summer, autumn and winter in the northern ranges, with a distinct spring minimum. The plains and foothills have more autumn—winter runoff, with slightly less in summer, and significantly less in spring.

2.2 Natural hazards

Some examples of recent significant natural events experienced in the Hunter region are detailed in Table 1.

Table 1: Recent significant natural events in the Hunter region

Event	Date	Estimated damage/cost*
Severe storm	8 June 2007	\$1,350 million (cost)
Bushfires	29 December 1993 – 17 January 1994	\$58 million (cost)
Hailstorm	31 October 2006	\$51 million (cost)
Severe storms and tornadoes	18–21 November 2001	\$29 million (cost)
Severe storm	22 June 1998	\$12 million (cost)

^{*} Emergency Management Australia estimates (EMA 2009) – cost is original dollar values.

It should be noted that in most cases the above phenomena were not unprecedented and were less intense than the highest magnitude events possible under present climatic conditions.

This section provides more detail on the severe storm on 8 June 2007 and the November 2001 tornadoes to demonstrate the kinds of impacts that recent significant natural hazards have had on the Hunter region.

In New South Wales, flash flooding, riverine flooding, hail, wind and coastal erosion due to very rough seas, are often associated with low-pressure systems off the eastern coast of Australia, as was the case with the severe storm on 8 June 2007. Known as East Coast Lows (ECLs), these systems occur on average 10 times each year. The severe storm on 8 June 2007 resulted from an intense ECL – the first of five over the Tasman Sea for that month alone – and ultimately led to more than 20,000 calls to the NSW State

Emergency Service (SES) over the following 17 days. The Australian Bureau of Meteorology (BoM) described this sequence of five ECLs as 'rare but not unprecedented'.

The 2007 storm saw large areas of the Hunter region subject to Natural Disaster Declarations with widespread flooding. Wind gusts reached 124 km/h at Nobbys Head, contributing to the 76,000 tonne bulk carrier *Pasha Bulker* running aground on Nobbys Beach, Newcastle. Rainfalls of 200–300 mm were common, leading to major flooding of the Hunter, Paterson and Williams rivers and the biggest floods since 1971 at Singleton and Maitland. Thousands of people were evacuated from Central Maitland, South Maitland and Lorn alone, and infrastructure was severely impaired with roads closed, rail lines damaged, gas supplies disrupted, and power cut to 200,000 users.

In the period 18–21 November 2001, tornadoes were observed accompanying severe storms in the Hunter region. Port Stephens was worst hit after tornadoes formed over the water (as water spouts) before travelling back across the land, with 100 business premises damaged in 20 minutes of winds up to 150 km/h and waves to 5 m. A small tornado was also reported inland at Rutherford on 19 November 2001.

3 Projected changes to climate and natural hazards in the Hunter region

The following section details projected changes to climate and the frequency and intensity of natural hazards in the Hunter region out to 2050. Projections for significant fire, coastal erosion and weather-related hazards in the Hunter region are based on those developed for the NSW Climate Impact Profile: the impacts of climate change on the biophysical environment of New South Wales (DECCW 2010). The NSW Climate Impact Profile projections were developed using current global climate model data provided by the Climate Change Research Centre at the University of New South Wales. Further research will be needed to improve the accuracy of these projections.

3.1 Projected changes to climate

Daily maximum temperatures in the Hunter region are projected to increase over all seasons by an average of 1–3°C, with the greatest increases in maximum temperatures in winter and spring (2–3°C) and the smallest increases in summer (1–1.5°C). Nights are also projected to be warmer by 2–3°C over all seasons in the east, and over all seasons in the west except during spring when the gain is projected to be 1.5–2°C.

Rainfall is projected to increase in all seasons except winter when it is likely to fall by 5–20% in the west. Increases at other times will be 5–50%, with the greatest gains likely in spring and summer. Despite projected rainfall increases, increased evaporation across all seasons in most of the region is likely to result in no net change in water balance for many areas. Overall, a slight increase in runoff is projected, with a substantial increase in summer and a minor increase in autumn to be followed by decreases in winter and spring.

Patterns of the El Niño—Southern Oscillation (ENSO) cycle and other climatic influences may be modified by global warming and this is an active area of research. Although large uncertainties exist regarding the future interactions of ENSO and other climatic influences, El Niño years experienced in the region are likely to continue to result in an increased probability of lower than average rainfall and become hotter. La Niña years experienced in the region are likely to continue to result in an increased probability of higher than average rainfall and become warmer, with storms producing heavy downpours likely to become more frequent.

3.2 Projected changes to natural hazards

The current resolution of global climate models means that relatively large damaging weather events such as ECLs are currently not captured. The Department of Environment, Climate Change and Water (DECCW) is leading a multi-institutional research initiative called the Eastern Seaboard Climate Change Initiative (ESCCI) to address specific research gaps. The first priority of ESCCI is to establish an ECL project to improve future projections.

In addition, little information is available for small scale, short-lived damaging weather events such as severe thunderstorms, which are not adequately captured in the resolution of climate models so that a low level of confidence

is associated with any projections of extreme winds. Further research is required to improve projections for changes to flood-producing rainfall events. Studies of triggering events such as severe thunderstorms, ex-tropical cyclones and troughs and broad scale weather systems resulting in flooding currently do not provide enough certainty for projections of frequency and intensity. The impacts of flooding at specific locations may have been assessed in flood investigations; however, many of the impacts of climate change on flood behaviour are yet to be investigated in detail. The exposure of individual locations to flooding and the associated impacts on flooding due to climate change are quite specific and need to be addressed by flood investigations in particular catchments and locations.

More detailed high resolution (spatial and temporal) information on future climate is required to improve certainty of projections of significant fire hazards. Understanding future changes to El Niño frequency and intensity is also a key research need, as is research on ignitions (lightning and human), and changes in moisture and elevated carbon dioxide levels on vegetation, as the degree to which vegetation fuel characteristics will change and affect fire regimes is unknown.

Factors affecting local shoreline positions such as sediment supply, near shore currents, and wave characteristics (height, period and direction) may change, and modelling at present is extremely coarse and relatively uncertain. Projections for global sea level rise are subject to ongoing refinement by the international scientific community.

Further research on all climate variables is ongoing and will be reviewed by the Intergovernmental Panel on Climate Change (IPCC) in the development of its Fifth Assessment Report (due for finalisation in 2014). This material will be reviewed following its release.

3.2.1 Fire (see *Table 2*)

The frequency of very high or extreme fire-risk days is projected to increase in the Hunter and across New South Wales. Increases in temperature, evaporation and high fire-risk days are likely to influence fire frequency and intensify fire danger levels across the region, and the fire season is likely to be extended.

Fire frequency likely to increase

The current return period for fires in the Hunter region is variable, ranging from 5 to 30 years across the majority of the region, but wetter forests may experience little or no fire. Out to 2050, fire frequency is likely to increase but the fire return period is likely to remain largely within the current range. These projections are regarded as conservative however, and may require revision after further research on the effect of climate change on the frequency and intensity of ENSO, ignition rates and fuel accumulation.

Weather conditions conducive to large, intense fires to increase

Peak fire dangers in the Hunter region are currently reached in spring/summer, and no major change is projected; however, intensification of fire danger levels within the existing season is projected, as current periods of prolonged drought, and days of high temperature and wind speed, and low humidity, may increase out to 2050.

Very high to extreme fire danger days per year to increase

Historically, the Hunter region experiences 10 very high to extreme fire danger days annually near the coast, and 10–15 inland. These will possibly increase by 10–50%. Potential days for prescribed burning (when fire danger levels are moderate to high) are currently more than 120 per year and these are projected to increase by up to 5%. This projection is based on the number of days where the Forest Fire Danger Index is potentially appropriate. Actual suitable days will also depend on fuel moisture, forecasts of unfavourable weather and other safety considerations.

Changes to fuel availability uncertain

Projections of future fuel availability are regarded as highly speculative at this time and major research is required to determine the future effects of changes in moisture levels and elevated carbon dioxide levels on fire regimes. Future change in fuel availability is the least certain of all the fire hazard indicators. Projected decreases in available moisture will possibly reduce litter and grass fuels in coastal regions and north, north-west mountain regions. Further expansion of lantana infestations may also decrease the flammability of forests, and changes to native grasses such as blady grass may also be important to future trends.

3.2.2 Wind (see *Table 3*)

High winds in the Hunter region are associated with a number of climatic systems including ECLs, severe thunderstorms, ex-tropical cyclones, and frontal systems.

Changes to frequency of ECLs uncertain

Historically ECLs are a dominant source of high winds for the region with an average of 10 systems per year, and 3–5 of these have severe coastal impacts. They generally occur between autumn and spring and are most frequent in winter, as was the case with the ECL which led to heavy flooding and gale force winds on 8–9 June 2007. Limited research means that changes in the frequency and intensity of ECLs out to 2050 are unknown; however, a proposed ECL project is designed to address the knowledge gap.

Changes to frequency of severe thunderstorms uncertain

Existing information on present day thunderstorm frequency is tied to those storms that generate hail, of which there are about eight that affect the Hunter region annually. However, a larger number of thunderstorms produce severe winds that can be in excess of 90 km/h. Severe thunderstorms occur from late spring through to autumn, and are summer dominant. Projections of wind speeds associated with severe thunderstorms out to 2050 are currently unavailable, as these weather events are not adequately covered by climate models.

Changes to incidence of tropical and ex-tropical cyclones uncertain

The incidence of tropical cyclones and ex-tropical cyclones producing severe winds in the Hunter region is historically low, and the projected changes are largely unknown. Studies have concluded that no significant change is likely in overall tropical cyclone numbers out to 2050, but there could be an increase in the proportion of systems in categories 3–5, depending on changes in sea surface temperature (SST) and upper atmosphere circulation.

Changes to incidence of gales and frontal systems uncertain

The incidence of gales and frontal systems is currently low to moderate, and some projected changes indicate a likely decline in the frequency of westerly gales as the winter westerly belt moves south. However, further development of daily wind speed modelling is required to improve the level of confidence for significant wind speed projections.

3.2.3 Hail (see *Table 4*)

Changes to frequency of hail days uncertain

The Hunter region on average is affected by eight hail-producing thunderstorms per year. These storms are significantly more common near the coast than over the inland. The hail season lasts from August to March, with the highest frequency between October and January, usually peaking in December. Further development of climatic models is required for projections of future frequency and intensity.

3.2.4 Lightning (see *Table 5*)

Changes to lightning frequency uncertain

The Hunter region currently has an average of 20 to 30 days per year which experience thunder, with a frequency of lightning strikes of 1–3/km²/year. Lightning strikes are more prevalent in the south and west of the region. They are summer dominant, but can occur at any time of the year. Projections under climate change are mostly unknown, but some studies have suggested a 5–6% change in global lightning frequency for every 1°C of global temperature change, and a possible increase in high based (dry) thunderstorms.

3.2.5 Flash flooding (see *Table 6*)

Incidence of flash flooding likely to increase

Flash flooding results from storms of relatively short duration and high intensity, with water both rising and flowing quickly. Current incidence is variable depending on location, but the risk is expected to increase with changing community profiles in urban areas, and in some cases due to rising sea levels because of climate change. Overall, further research will be needed to provide more specific projections on the potential scale of changes to these flood-producing rainfall events. The proposed ECL project will assist in addressing some of the research gaps, as ECLs, along with fairly rare ex-

tropical cyclones and severe thunderstorms, are among the current main causes of flash flooding.

3.2.6 Riverine flooding (see *Table 7*)

Incidence of riverine flooding may increase

Vulnerability and exposure to riverine flooding varies significantly with location, but is expected to increase with changing community profiles out to 2050 due to density of development and to any increase in exposure to flood-producing storm events. Exposure to this hazard is also expected to increase in settlements around the catchments in lower coastal areas and coastal lakes and lagoons of the Hunter region, where a combination of raised ocean levels and catchment flooding can be the controlling flood mechanism. Again, further research will be needed to provide more specific advice on the potential scale of changes to the significant rainfall events that produce floods. The proposed ECL project will assist in addressing some of the research gaps as ECLs, along with fairly rare ex-tropical cyclones, severe thunderstorms and troughs, are among the current main causes of riverine flooding. The impact of sea level rise and changing flood-producing rainfall behaviour on riverine flooding will need to be assessed at specific locations due to its impacts on local flood behaviour and variations between communities in their exposure to flood risk.

3.2.7 Heatwaves (see Table 8)

Heatwaves have the potential to cause a significant number of human casualties, particularly among the elderly and very young. Heatwaves have accounted for more deaths in Australia than any other natural hazard. For the purposes of this profile, heatwaves are defined as at least three consecutive days with maximum temperatures above the 90th percentile for the month.

In the Hunter region, the frequency of heatwaves has historically been higher in the west of the region where temperatures are also higher. In the period 1979 to 2008, the region experienced 16 spring and 8 summer heatwave events in Newcastle; while at Scone, the figures were 28 in spring, 20 in summer and 11 during March.

Frequency and intensity of heatwaves to increase

Heatwaves are projected to become more severe because of higher temperatures as a result of climate change. They are also likely to become more frequent, but projections are dependent on mid-latitude circulation patterns.

3.2.8 Coastal erosion and inundation (see *Table 9*)

Sea level rise to increase

According to the IPCC, global sea levels are rising and globally rose by an estimated 17 cm (± 5 cm) during the 20^{th} Century (IPCC 2007). Satellite measurements indicate that global sea levels have risen by around 3.2 mm (± 0.4 mm) per year since 1992. A maximum rise of 40 cm relative to 1990 sea levels by 2050 is projected for New South Wales, with the next update in global projections to be released by the IPCC in 2014.

Still water level to increase

Factors such as astronomical tides and variations in meteorological conditions including winds and barometric pressure are included in still water level measurements. At present, an average still water level of 1.435 m Australian Height Datum (AHD) is estimated to occur once every 100 years at Fort Denison. By 2050, assuming a rise in mean sea level of 40 cm (relative to 1990) this water level is expected to occur as frequently as once every 18 days. Assuming an equivalent rise in mean sea level, by 2050 a still water level of 1.815 m AHD is estimated to occur once every 100 years. These projected changes to the still water level are based purely on changes due to sea level rise. Research suggests that a 1% increase in storm surge is possible, in addition to projected sea level rise, but the effects of climate change on these factors are not yet adequately known.

Wave height and period to change

The Hunter region experiences an average wave climate of 1–2 m from the south-east. Based on 22.2 years of wave data collection from the Crowdy Head offshore waverider buoy, significant wave heights exceeding 7.0 m for a period of up to 12 hours are likely to be experienced once every 100 years, with a 1 hour significant wave height of 8.6 m having an equivalent 100 year recurrence interval. An 8% increase in the maximum storm wave height and period is projected out to 2050 for waves arriving from the southerly, easterly and south-easterly directions. In northern New South Wales the frequency of swell waves is projected to increase, while in the south of the state that frequency is projected to decrease. Major research such as the ECL project is required to improve projections.

Change to shoreline recession rates due to underlying processes uncertain

A combination of underlying factors including wave characteristics (particularly wave direction), beach orientation, presence of control features (such as bedrock, headlands and entrance breakwater structures) and sediment transport processes currently contribute to shoreline recession in the Hunter region by 0–1.0 m/year. Future rates of shoreline recession may vary as a result of climate change, but the nature and extent of that change out to 2050 is not currently known. In addition, embedded within current measured rates of shoreline recession is a component attributable to historical sea level rise. Further research is needed to de-couple the sea level rise component from measured recession.

Shoreline recession due to sea level rise to increase

Historical sea level rise is estimated to contribute to sandy shoreline recession by 0.15–0.3 m/year, based on a rate of global average sea level rise of approximately 3 mm/year. A projected rise in sea level of up to 40 cm out to 2050 is likely to result in a recession of sandy parts of the coastline of up to 20–40 m. These changes in shoreline position are based on a general rule of thumb (the 'Bruun rule'), and detailed study at individual locations is required for more accurate projections.

Sea level rise may increase the potential coastal impacts from tsunamis

Ocean tsunamis are not driven by meteorological processes; however, their impacts are directly influenced by the proximity of people and property to coastal water level. The entire coast of New South Wales is known to be exposed to tsunamis. The effect of a tsunami reaching the coast can range from so slight as to be unnoticed, to an event large enough to overtop coastal dunes and waterfronts to inundate low-lying coastal land. The actual risk of tsunami inundation is currently under investigation for the SES. As of August 2009 the extent of inundation and indicative probability of tsunami events was not established with any confidence for any locations. However, it can be reasonably inferred that any low-lying coastal location which has a vulnerability to coastal inundation due to estuarine flooding or storm surge, or any area identified as a coastal erosion hot spot, will have a vulnerability to tsunami inundation.

Table 2: Hunter fire hazard indicators

Indicator	Current conditions	Projected change (to 2050)	Status of research
Frequency range	Variable – the fire cycle is 5–30 years across the bulk of the region. Wetter forests, including rainforest, may experience little or no fire.	Increased frequency of fire likely but the fire cycle will remain largely within this range.	Some detailed analyses of current fire regimes are available for this region. More detailed high resolution (spatial and temporal) information on future climate required. Understanding future changes to ENSO frequency and intensity is a key research need. Research on ignitions (lightning and human) is required.
Season of peak fire danger	Spring – summer.	No major change projected.	See above.
Potential days for prescribed burning (i.e. average annual days of moderate – high fire danger)	>120 days.	Projected increase (1–5%).	See above.
Average number of days (per annum) of very high – extreme fire danger	10 near coast. 10–15 inland.	A 10–50% increase is possible.	See above.
Weather conditions conducive to large, intense fires	Prolonged drought. Days of high temperature and wind speed, plus low humidity.	The incidence of these conditions may increase (see above).	Some detailed analyses of weather conditions associated with large fires are available for this region. Future trends – see above.

Indicator	Current conditions	Projected change (to 2050)	Status of research
Influence of runoff on water availability (average seasonal trends)	The peak tends to be evenly spread through summer, autumn and winter – particularly in the ranges. Lowest runoff is in spring.	Increases in summer/autumn and decreases in winter/spring (prior to the fire season) are projected.	See above.
Fuel	Predominantly litter fuels in dry sclerophyll woodland/forest. Grassy fuels are important in woodlands and forests throughout the region and in agricultural land. Lantana infestations are common in forests.	Projected decrease in available moisture could reduce litter and grass fuels in coastal regions and north, north-west mountain regions. Further expansion of lantana may also decrease the flammability of forests. Exotic grasses have the potential to alter fire regimes. Changes to native grasses such as blady grass may also be important.	Major research effort required to resolve future effects of changes in moisture and elevated CO ₂ on plant growth, litter accession, decomposition, plus overall changes to vegetation structure (cover and woody/herbaceous plant balance). Projections are currently highly speculative and the degree to which vegetation fuel characteristics will change and affect fire regimes is unknown. Further research on the spread of exotic species such as lantana required.

Table 3: Hunter wind hazard indicators

Meteorological source	Indicator	Current conditions	Status of research
East Coast Low	Frequency	Average of 10 per year.	Existing research is very limited and is yet to give a consistent projection for changes to ECLs under enhanced greenhouse gas conditions beyond 2050
	Intensity	3–5 per year produce severe coastal impacts with gale force winds. The ECL on 8–9 June 2007 led to heavy flooding in this region and gale force winds, including the grounding of the Pasha Bulka off Newcastle beach.	(McInnes <i>et al.</i> 1992; Hennessy <i>et al.</i> 2004; Abbs and McInnes 2004). A proposed ECL research project is the first priority for the Eastern Seaboard Climate Change Initiative (ESCCI) and is designed to address research gap.
Seasonality Autumn through spring. Winter dominant.			
Severe thunderstorm	Frequency	An average of 8 storms with severe winds affect the Hunter valley each year, particularly along the coast.	Research is currently limited to only a couple of studies for NSW: Schuster et al. 2005; Leslie et al. 2007. CSIRO (2007a) states that severe thunderstorms are not adequately captured by the resolution of current climate models. Future work to improve these models is therefore required to improve projections for extreme winds associated with severe thunderstorms.
	Intensity	Severe thunderstorms can produce wind gusts of 90 km/h or greater.	There is currently no published work on observed trends in intensity. Future research is required to develop models capable of resolving these relatively small scale phenomena and therefore providing future projections.
	Seasonality	Late spring through to autumn, particularly from November to February. Peak frequency in December, with ~2 events per year.	

Meteorological source	Indicator	Current conditions	Status of research
Ex-tropical cyclone	Frequency	Low – only a few recorded crossings into NSW of decaying cyclones from the Pacific or the Gulf of Carpentaria.	No significant change in East Coast cyclone numbers projected to 2050 (Abbs <i>et al.</i> 2006; Leslie <i>et al.</i> 2007; Walsh <i>et al.</i> 2004). Likely to be highly dependant on the level of emissions and the magnitude of SST changes and upper atmosphere circulation changes.
	Intensity	Severe winds can result from these low frequency events.	Increase in proportion of categories 3–5 systems in the modelling studies above. These studies do not provide, with any certainty, projections for the frequency and intensity of systems over NSW latitudes. Likely to be highly dependant on SST changes and upper atmosphere circulation changes.
Gales and frontal systems		Low to moderate.	Only a small number of models provide daily wind speed data from which extremes can be estimated. Therefore further development is required to improve the level of confidence associated with any extreme wind speed projections.
			Several models indicate a likely decline in the frequency of westerly gales as the winter westerly belt moves further south.

Table 4: Hunter hail hazard indicators

Indicator	Current conditions	Status of research
Frequency	The Hunter region experiences an average of 8 thunderstorms with hail per year, including on average 1 per year with hail exceeding 5 cm in diameter. These are more common in coastal regions, with only 3 events within 25 km of Scone but 33 within 25 km of Newcastle, during the period 1990–2007. Schuster et al. (2005) reported a decline of 30% in the number of hailstorms affecting Sydney in the period 1989–	The CSIRO Mark 3.5 model for Special Report on Emissions Scenarios (SRES) A2 scenario suggests a significant increase in hail days over the Sydney area; an increase of around 6 hail days per year by 2070 (CSIRO 2007a). Research is currently limited to only a couple of studies for NSW: Schuster et al. 2005; Leslie et al. 2007; Niall and Walsh 2005. CSIRO (2007a) states that severe thunderstorms are not adequately captured by the resolution of the climate models. Future work to improve
	2002 compared with 1953–1988. Kuleshov <i>et al.</i> (2002) found no such decline.	these models is therefore required to improve projections for extreme winds associated with severe thunderstorms.
Intensity	Severe thunderstorms can produce hail over 2 cm in diameter. The most severe hailstorm in this area from 1990–2007 had 12 cm hail at Muswellbrook on 24 October 2004.	There is currently no published work on observed trends in intensity. Future research is required to develop models capable of resolving these relatively small scale phenomena and therefore providing future projections.
Seasonality	The hail season lasts from August to March, with highest frequency between October and January, particularly December.	

Table 5: Hunter lightning hazard indicators

Indicator	Current conditions	Status of research
Frequency	Average of 20–30 thunder days per year in the Hunter area (Kuleshov <i>et al.</i> 2002).	Currently no research for the Australian region of expected changes to lightning under enhanced greenhouse conditions. Some studies such as Price and Rind (1992) have suggested a 5–6% change in global lightning frequency for every 1°C global temperature change. US studies have also indicated that there may be an increase in high based (dry) thunderstorm activity. The regional scale effects on lightning for NSW are unclear.
Intensity/scale	Average of 1–3 per km ² per year (ground flash).	
Distribution		
Seasonality	Summer dominant but can occur at any time of the year.	

Table 6: Hunter flash flooding hazard indicators

Meteorological source	Indicator	Current conditions	Status of research
All types of relatively short duration storms	Vulnerability of people and property to above floor flooding in urban areas where no specific flood warnings are able to be provided and flooding rises and can flow quickly	Varies significantly with exposure of specific locations or communities to flooding. Can be derived from a range of weather events including thunderstorms and ECLs. Expected to increase with the changing community profiles and any change in scale of events.	Future research needs to be undertaken to provide more specific advice on potential scale of changes to these flood-producing rainfall events.
	Exposure	Significant, widespread exposure varying with location. Increasing due to changes in density of development and any increase in exposure to flood-producing storm events discussed below. The exposure of individual locations to flooding are quite specific and need to be addressed by flood investigations in specific catchments and locations. Studies have been undertaken to examine existing risks in many areas but other areas remain unstudied. In catchments in lower coastal areas a combination of raised ocean levels and catchment flooding can be the controlling flood mechanism.	Assessment of climate change impacts of sea level rise and flood-producing rainfall events is necessary for specific locations. Research needs to be undertaken to provide more specific advice on potential scale of changes to these flood-producing rainfall events.

Meteorological source	Indicator	Current conditions	Status of research
East Coast Low	Frequency	Average of 10 per year.	Very limited literature: McInnes <i>et al.</i> 1992; Hennessy <i>et al.</i> 2004; Abbs and McInnes 2004.
			These studies are yet to give a consistent projection for changes to ECLs beyond 2050.
			The proposed ECL research project is the first priority for the ESCCI and is designed to address this research gap.
	Intensity	Average of 3–5 per year produce severe coastal impacts with flooding.	
	Seasonality	Autumn through spring. Winter dominant.	No change likely as they require a strong temperature gradient between a cold land surface and warm inshore sea surface temperatures for development.
Ex-tropical cyclone	Frequency	Low – only a few recorded crossings into NSW of decaying cyclones from the Pacific or the Gulf of Carpentaria.	Likely to be highly dependant on SST changes and upper atmosphere circulation changes.
			Abbs et al. 2006; Leslie et al. 2007; Walsh et al. 2004.
			No significant change in East Coast cyclone numbers projected to 2050.
	Intensity	Heavy rainfall can result from these low frequency events.	Likely to be highly dependant on SST changes and upper atmosphere circulation changes.
			Increase in proportion of categories 3–5 systems in the modelling studies above. These studies do not provide, with any certainty, projections for the frequency and intensity of systems over NSW latitudes.

Meteorological source	Indicator	Current conditions	Status of research
Severe thunderstorm	Frequency	On average, severe thunderstorms produce flash flooding several times per storm season though the location of impact within the region would vary.	Limited to only a couple of studies for NSW: Schuster <i>et al.</i> 2005; Leslie <i>et al.</i> 2007. CSIRO (2007a) states that severe thunderstorms are not adequately captured by the resolution of the climate models. Future projections for extreme winds associated with severe thunderstorms are therefore currently unavailable.
	Intensity	On average, severe thunderstorms produce flash flooding several times per storm season.	There is no published work on observed trends in intensity. Models are currently unable to resolve these relatively small scale phenomena and are therefore unable to provide future projections.
	Seasonality	Late spring through to autumn. Summer dominant.	

Table 7: Hunter riverine flooding hazard indicators

Meteorological source	Indicator	Current conditions	Status of research
All types of relatively short duration storms	Vulnerability of people and property to above floor flooding from rivers	Varies significantly with exposure of specific locations or communities to flooding. Expected to increase with the changing community profiles and any change in scale of events.	Can be derived from a wide range of weather events including thunderstorms and ECLs, tropical cyclones and troughs. Research needs to be undertaken to provide more specific advice on potential scale of changes to these flood-producing rainfall events.
	Exposure	Significant, widespread but varies with location. Increasing due to changes in density of development and any increase in exposure to flood-producing storm events discussed below The exposure of individual locations to flooding is quite specific and needs to be addressed by flood investigations in specific catchments and locations.	Assessment of climate change impacts of sea level rise and flood-producing rainfall events is necessary for specific locations. Research needs to be undertaken to provide more specific advice on potential scale of changes to these flood-producing rainfall events.
		Studies have been undertaken to examine existing risks in many areas but other areas remain unstudied.	
		In catchments in lower coastal areas a combination of raised ocean levels and catchment flooding can be the controlling flood mechanism.	

Meteorological source	Indicator	Current conditions	Status of research
East Coast Low Frequency Average of 10 per year.		Average of 10 per year.	Very limited literature: McInnes <i>et al.</i> 1992; Hennessy <i>et al.</i> 2004; Abbs and McInnes 2004.
			These studies are yet to give a consistent projection for changes to ECLs beyond 2050.
			The proposed ECL research project is the first priority for the ESCCI and is designed to address this research gap.
		On average, 3–5 per year produce severe coastal impacts with flooding.	
	Seasonality	Autumn through spring. Winter dominant.	No change likely as they require a strong temperature gradient between a cold land surface and warm inshore SST for development.
Ex-tropical cyclone	Frequency	Low – only a few recorded crossings into NSW of decaying cyclones from the Pacific or the Gulf of Carpentaria.	Likely to be highly dependant on SST changes and upper atmosphere circulation changes.
			Abbs et al. 2006; Leslie et al. 2007; Walsh et al. 2004.
	Intensity	Heavy rains can result from these low frequency events.	Likely to be highly dependant on SST changes and upper atmosphere circulation changes.
			Increase in proportion of categories 3–5 systems in the modelling studies above. These studies do not provide, with any certainty, projections for the frequency and intensity of systems over NSW latitudes.
Trough systems	Trough systems Frequency Unknown.		Unaware of any Australian research on how trough systems will respond to enhanced greenhouse gas conditions. This is an obvious research gap.
	Intensity	Unknown.	

	Meteorological source	Indicator	Current conditions	Status of research
Seas		Seasonality	Can occur at any time of year but most prevalent in the October to March period with summer dominance.	

Table 8: Hunter heatwave hazard indicators

Indicator	Current conditions	Future research required
Frequency	Over the period 1979–2008: Newcastle – 16 in spring, 8 in summer. Scone – 28 in spring, 20 in summer, 11 in March.	Frequency of heatwaves is expected to increase, however this is dependent on mid- latitude circulation patterns and these have not yet been confidently projected to 2050. Research limited by lack of a consistent and relevant definition for heatwaves. BoM, DECCW and NSW Department of Health (NSW Health) are working on developing a heatwave definition relevant to human health and morbidity. The definition used for this assessment has been 3 consecutive days with maximum temperatures above the 90 th percentile for the month. This definition is yet to be tested against human morbidity studies in NSW as these are yet to be published by NSW Health.
Intensity	At least 3 consecutive days above the 90 th percentile for maximum temperatures during 1979–2008. Longest heatwave at Scone was 10 days, starting 6 February 2004, with a maximum temperature of 41.4°C.	By 2050 maximum temperatures will increasingly exceed the 1979–2008 90 th percentile. Mean maximum temperature increases of 1–3°C are likely. Heatwaves are usually associated with extreme heat days with exceedingly high temperatures (far greater than 1–3°C rise in mean maximum temperatures expected). It is clear that when a heatwave does occur the maximum temperatures involved are likely to be much higher than they currently are. The severity of heatwaves is almost certain to increase, whilst the frequency is still to be evaluated properly. Research into extreme temperature projections for eastern Australia is very limited.
Distribution	More prevalent in western regions, which also have higher mean temperatures.	The importance of the sea breeze in curtailing heatwaves is evident in the reduction in heatwave frequency on the eastern coast of the Hunter region.
Seasonality Spring and summer.		Research needed to better understand early season high temperatures and their frequency. Single significantly above average hot days in early spring and summer can have a considerable effect on morbidity and mortality.

Table 9: Hunter coastal erosion and inundation hazard indicators

Indicator	Current conditions	Projected change (to 2050)	Status of research
Sea level rise	Total 20 th century global sea level rise (SLR) estimated to be 17 ± 5 cm (IPCC 2007). Global average eustatic SLR over the period from 1961 to 2003 is estimated at 1.8 ± 0.5 mm/yr (IPCC 2007). Global SLR measured from satellite altimeters post-1992 at around 3.2 ± 0.4 mm/year (University of Colorado 2009).	An upper limit of SLR of 0.4 m relative to 1990 levels.	Projections of SLR are continually refined by the international community and released by the IPCC. Updated projection of SLR will next be released in 2014.
Still water level (Sydney Harbour still water level data and analyses have been used as a surrogate for the Hunter Coast due to the quality of the data and length of record)	1.435 m AHD 100 year Average Return Interval (ARI) design still water levels based on Fort Denison data from 1914 to present (Watson and Lord 2008). Still water level includes components due to astronomical tides and variations due to meteorological conditions (including winds, barometric pressure, etc.).	1.815 m AHD 100 year ARI design Sydney Harbour still water level based on upper range SLR (Watson and Lord 2008). Today's 100 year ARI design still water level of 1.435 m AHD is projected to have an ARI of 0.05 by 2050, equivalent to occurring once every 18 days, based on upper range SLR (Watson and Lord 2008). A 1% increase in storm surge is projected but within errors of present day storm surge estimates (CSIRO 2007b). Not appropriate for planning but acceptable for sensitivity analysis.	Changes to the still water level ARI are purely based on changes due to SLR (including regional changes due to water temperature). Changes to storm intensity and local changes in barometric pressure may also affect still water levels. The effect of climate change on these factors is not yet adequately known.

Indicator	Current conditions	Projected change (to 2050)	Status of research
Wave characteristics (height, period and direction)	1-hour 100 year ARI significant wave height is 8.6 m. 12-hour 100 year ARI significant wave height is 7.0 m (based on 22.2 years of record from Crowdy Head offshore waverider buoy, MHL 2009). Dominant storm wave direction is from the south-east to south.	An 8% increase in the maximum storm wave height and period from the southerly, easterly and south-easterly directions. Not appropriate for planning but acceptable for sensitivity analysis. In northern NSW the frequency of occurrence of swell waves is projected to increase, while in southern NSW the frequency of occurrence of swell waves is projected to decrease.	The mechanisms that generate extreme wave heights are not resolved by GCMs. Proposed research on ECLs and their change in frequency under future climate is planned and should provide better projections of changes.
		This data is based on Global Climate Models (GCMs) which do not model meso-scale climate systems that generate waves along the NSW east coast.	
Shoreline recession (underlying process driven)	0-1.0 m per year. These present day rates of shoreline recession currently contain changes due to historical sea level rise. Further research to de-couple the SLR component is required.	Unknown. The effect of climate change on the processes that drive underlying shoreline recession are poorly understood and require further research.	Changes in local shoreline position are highly variable and determined by a range of factors including local sediment supply, nearshore currents, wave characteristics (height, period and direction). There may be changes to these factors, which may affect recession rates into the future, however current modelling on these is extremely coarse and relatively uncertain on these aspects.
Shoreline recession due to sea level rise	0.15–0.3 m per year (based on use of the Bruun rule and assuming current global average SLR at 3 mm per year and active profile slope of 1:50 – 1:100).	20–40 m (relative to present day and based on Bruun rule assuming SLR over the period to be 0.4 m with active profile slope ranging from 1:50 – 1:100).	

4 References

Abbs, D, Aryal, S, Campbell, E, McGregor, J, Nguyen, K, Palmer, M, Rafter, T, Watterson, I and Bates, B (2006). *Projections of extreme rainfall and cyclones*, report to the Australian Greenhouse Office, Canberra.

Abbs, DJ and McInnes, KL (2004). The impact of climate change on extreme rainfall and coastal sea levels over south-east Queensland, part 1 of an analysis of extreme rainfall and wind events in a GCM, a project undertaken for the Gold Coast City Council, CSIRO Atmospheric Research, Aspendale, Vic.

CSIRO, Australian Bureau of Meteorology (2007a). Climate change in Australia: technical report 2007, CSIRO.

CSIRO, McInnes, KL, Abbs, DA, O'Farrell, SP, Macadam, I, O'Grady, J and Ranasinghe, R (2007b). *Projected changes in climatological forcing for coastal erosion in NSW*, CSIRO.

Department of Environment, Climate Change and Water (2010). NSW Climate Impact Profile: the impacts of climate change on the biophysical environment of New South Wales, Department of Environment, Climate Change and Water, Sydney South, NSW.

EMA (2009). Emergency Management Australia disasters database, accessed July 2009, http://www.ema.gov.au/www/emaweb/emaweb.nsf/Page/ResourcesDisasters_Database

Hennessy, K, McInnes, K, Abbs, D, Jones, R, Bathols, J, Suppiah, R, Ricketts, J, Rafter, T, Collins, D and Jones, D (2004). Climate change in New South Wales, Part 2: Projected changes in climate extremes", consultancy report for the New South Wales Greenhouse Office, CSIRO.

IPCC (2007). Climate change 2007: the physical science basis, contributions of Working Group 1 to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change [Solomon, S, Qin, D. Manning, M, Chen, Z, Marquis, M, Averyt, KB, Tignor, M and Miller, HL (eds.)], Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA.

Kuleshov, Y, de Hoedt, G, Wright, W, and Brewster, A (2002). 'Thunderstorm distribution and frequency in Australia', *Austral Meteor Mag*, vol. 51, pp. 145–154.

Leslie, LM, Karoly, DJ, Leplastrier, M and Buckley, BW (2007). 'Variability of tropical cyclones over the southwest Pacific Ocean using a high resolution climate model', *Meteorology and Atmospheric Physics*, vol. 97, pp. 171–180.

McInnes, KL, Leslie, LM and McBride, JL (1992). 'Numerical simulation of cut-off lows on the Australian east coast: sensitivity to sea-surface temperature and implications for global warming', *Int. J. Clim.*, vol. 12, pp. 783–795.

MHL (2009). Manly Hydraulics Laboratory waverider buoy data, provided to DECCW in 2009, Manly Hydraulics Laboratory, Manly.

Niall, S and Walsh, K (2005). 'The impact of climate change on hail storms in southeastern Australia', *Int. J. Climatology*, vol. 25, pp. 1933–1952.

Price, C and Rind, D (1992). 'A simple lightning parameterization for calculating global lightning distributions', *Journal of Geophysical Research*, vol. 97 (1992), pp. 9919–9933.

Schuster, S, Blong, R and Speer, M (2005). 'A hail climatology of the greater Sydney area and New South Wales, Australia', *Int. J. Climatol.*, vol. 25, pp. 1633–1650.

University of Colorado at Boulder (2009). Sea level change: 2009 release #2, accessed April 2009, http://sealevel.colorado.edu/

Walsh, KJE, Betts, H, Church, J, Pittock, AB, McInnes, KL, Jackett, DR, McDougall, TJ (2004). 'Using sea level rise projections for urban planning in Australia', *Journal of Coastal Research*. vol. 20 (2), pp. 586–598.

Watson, PJ and Lord, DB (2008). Fort Denison Sea Level Rise Vulnerability Study, a report prepared by the Coastal Unit, NSW Department of Environment and Climate Change, Sydney South, NSW.